

THEOLOGICAL CONTROL OF THE PROPERTY OF THE PRO

TAD AND TROWN (DAN THE SEE PRESENTS SHAND (COME)

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

December 09, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/513,355

FILING DATE: October 22, 2003

RELATED PCT APPLICATION NUMBER: PCT/US04/35363

Certified by



Jon W Dudas

Acting Under Secretary of Commerce for Intellectual Property and Acting Director of the U.S. Patent and Trademark Office

Docket Number: | 717-031951

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

#### PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail	Label No. EL	971287301	1 US							
			INVEN	TOR(S)				·		
Resider  Given Name (first and middle [if any]) Family Name or Sumame (City and either State or						sidence ate or Foreign	n Country	)_		
Albert J.		Hillsborough, NC								
Melissa Marie	,			Carrboro	, NC					
Additional invent	ors are being name	ed on the _	sepai	rately numbered s	sheets a	attached he	ereto			
	TITL	E OF TH	E INVENT	TION (500 chara	cters n	nax)				
Automate	d System for Im	naging Ar	tificial Ti	ssue Construct	s in a	Controll	ed Env	ironment		
Direct all correspondence	10:	CORR	ESPONDE	NCE ADDRESS						_
X Customer Numbe	r 2	8289	-		ļ	Place Cus	tomer N	lumber		
OR	Type Custon	mer Numbe	r here			Bar Code	Label h	ere	P.T0	
Firm or Individual Name	Webb Ziesenhe	im Logsdo	n Orkin & l	Hanson, P.C.					1.S.	12.2.T
Address	700 Koppers Bu	uilding								<u>.</u>
Address	436 Seventh Av	enue .							553	<u> </u>
City	Pittsburgh		State	Pennsylvania		Zip	15219		<u> </u>	
Country	U.S.A.		Telephone	412-471-8815		Fax	412-47	1-4094		
	ENCLO	SED APP	LICATION	N PARTS (check	all the	at apply)				
X Specification Nur	nber of Pages	2		CD(s), Nur	mber					_
X Drawing(s) Numb	per of Sheets 3	33		Other (spec	cify)					1
=	Sheet. See 37 CF	R 1.76	·			L				
METHOD OF PAYME	NT OF FILING F	EES FOR	THIS PRO	VISIONAL APPI	LICAT	ION FOR	PATEN	Т		
X Applicant claims sr	nall entity status. Se	e 37 CFR 1.	.27.			FILI	NG FE	E		
X A check or money	order is enclosed to o	over the fili	ng fees		_	AMO	TNUO	(\$)		
	is hereby authorized verpayment to Depos			23-0650		\$8	30.00			
Payment by credit of	ard. Form PTO-203	38 is attache	d.		_	L		j		
The invention was made by United States Government		nited States	Government	or under a contract	with an	agency of t	the			
X No.										
Yes, the name of the U	J.S. Government agency	y and the Gov	emment contra	act number are:						
Respectfully submitted,				Date	Octo	ber 22, 200	)3			_
	and	7			STRA	TION NO.	$\top$	43,01	6	_
SIGNATURE	1///14		:		f appro	priate)	<u></u>	·		=
TYPED or PRINTED N	IAME Nathan	J. Prepelka	1				1	021061		

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

TELEPHONE \_

412-471-8815

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the PTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commence, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

#### PATENT APPLICATION

#### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE APPLICATION OF:	ATTORNEY'S DOCKET NUMBE					
ALBERT J. BANES and MELISSA MARIE MALONEY	717-031951					
	NG ARTIFICIAL TISSUE CONSTRUCTS LED ENVIRONMENT					
Mail Stop PROVISIONAL PATENT APPLI Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450	CATION					
EXPRESS MA	AIL CERTIFICATE					
"Express Mail" Label NumberEL 971287	301 US					
Date of Deposit October 22,	2003					
I hereby certify that the following atta	ached paper or fee					
<ul> <li>PROVISIONAL APPLICATION</li> <li>SPECIFICATION (2 pp.)</li> <li>DRAWINGS (33) SHEETS</li> <li>CHECK FOR \$80.00</li> </ul>	FOR PATENT COVER SHEET (1 p. in trip.)					
is being deposited with the United States Posta service under 37 C.F.R. §1.10 on the date indi for Patents, Alexandria, VA 22313-1450.	al Service "Express Mail Post Office to Addressee" cated above and is addressed to the Commissioner					
Linda C						
(Typed name o	of person mailing paper or fee)					
Signature of p	Leguerson maining paper or fee)					

#### AUTOMATED SYSTEM FOR IMAGING ARTIFICIAL TISSUE CONSTRUCTS IN A CONTROLLED ENVIRONMENT

#### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

[0001] The system of the present invention is directed to a computer-implemented method and system for imaging tissue constructs in a controlled environment in the field of tissue engineering and cell biology, but could be used in any applications where programmable, automated imaging functions would be useful.

#### 2. Background of the Invention

[0002] In the field of tissue engineering, changes in 3D cell-matrix constructs over time are frequently studied. Typically, the cells within these constructs will begin to form attachments within a day after plating and will reorganize and contract the matrix within a few days. Measurements of matrix contraction under the influence of various physical and biochemical factors indicate the impact of each factor on cellular function.

[0003] Currently, measurements of matrix contraction are performed manually by periodically moving the culture plates from their controlled environment (inside an incubator) to access an external imaging device (camera or scanner). Depending on the effect being measured, this process may need to be repeated every few hours, day and night, for several days. In addition to being labor intensive, this process is also less than ideal for the cell cultures themselves. Preferably, the contraction of the constructs would be monitored without repeatedly exposing the constructs to dramatic environmental changes.

#### **DESCRIPTION OF THE INVENTION**

[0004] The system of the present invention incorporates an imaging device and a software program, which together allow the user to automatically monitor matrix contraction without removing the cell cultures from the incubator (see Figure 1). The scanner is set up inside the incubator with the cell culture plates placed on the scanner glass and the controller (computer with custom software, see Figure 2) connected and running nearby. The user inputs the desired scanning parameters (filename and type, resolution, etc), selects the scan area, and creates a scanning regimen. Once the program is launched, it will automatically initiate scans at the times indicated by this regimen, and the culture plates need only be removed from the incubator for steps such as media changes (in lengthy studies). The images are stored to a user-designated folder for future analysis or may, with additional computer processing, be automatically analyzed. Multiple imaging devices can be controlled from a

single computer/application to increase the number of culture plates that can be monitored. With the appropriate imaging devices and lighting variations (visible light, IR, UV), this application could also be extended to monitor changes at the cellular level, including performing analyses based on color distinctions. Block diagrams of the scanning function software (Figs. 3-9) and frequency set up software (Figs 10-17) are attached.

[0005] The computer-implemented method and automated system is embodied in the form of an executable software program, preferably with a Graphical User Interface (GUI). The user interfaces with the GUI and interacts with the method and system of the present invention. The software program of the present invention may also interact with or execute using other enabling and/or proprietary software, such as LabVIEW<sup>TM</sup> by National Instruments. Various screenshots of the present computer-implemented method, executing in conjunction with LabVIEW<sup>TM</sup>, are illustrated in Figs. 18-27.

#### **EXAMPLE**

Various illustrations, photographs, charts and text created in connection with the [0006] following example are illustrated in Figs. 28-34. Human tendon internal fibroblasts (HTIF, 2 x 10<sup>5</sup> cells/100 µl/specimen) were plated in linear, tethered, collagen gels in TISSUE TRAIN<sup>TM</sup> culture plates. After two hours, when the gels had solidified, the culture plates were removed from the FX-4400TT TISSUE TRAINTM Culture System and placed on the glass of a Plustek OpticPro U24 flatbed scanner. The scanner was configured to collect images every hour for the first four hours of each day and every two hours for the remainder of the day, for four days. Culture plates were only removed from the incubator once a day to change the medium. Images were imported into SigmaScan Software to quantify the area of each gel at each time point. Gels experienced the greatest rate of contraction (58.6%) in the first 24 hours, and continued contracting to a total of 73.6% by the end of Day 4. The measured contraction of the gels followed a trend consistent with contraction results obtained by traditional methods. Besides simplifying the monitoring process, however, experimental results should be more accurate with automated imaging. Any confounding results deriving from changes in temperature/pH are minimized when the cultures can remain in the incubator during imaging. Additionally, the increased number of data points collected improves the resolution of the contraction curve and strengthens the findings. This method can easily be applied to perform contraction analysis with other 3D gel systems, as well.




Figure 1: Components of Imaging System






Figure 2: Flowchart of one simple embodiment of the software function


#### !GUI-Flexcell Scan. vi


#### Block Diagram




!GUI-Flexcell Scan. vi










!GUI-Flexcell Scan. vi









#### JGUI-Flexcell Scan. vi






Figb


·!ĠUI-Flexcell Scan.vi





#### !GUI-Flexcell Scan. vi




!GUI-Flexcell Scan. vi












GUI-Flexcell Frequency Setup.vi













F19 7










F1317










63








our-riexcell Frequency Setup. Vi














			Paths Paths			
	Librar	y Directory*	<u> </u>	] <b>  </b>	fault.	
					A:	
	Branes					
	GREET BETALL	MSCG	ATE	Pedia		Renover
		УK .	Cancel		# Help →	
<b>℃</b> ha	inges to this o	ption will take e	ffect the n	ext time you	start ⊫ab⁄n	ew.y


Fig. 19

Gategory:	General		
iGUI FlexcellMain vi e			
Location: C./IFIexce	   Scanner/Scannex.exe\	GUI Elexcel Main vi 🥴 🕏	
Gurrent Revision: 5.07			
OK	Gancel S	Web 2	

Fig. 20

a Category: :	Memory	Usage	Ţ	
Front Pane	l'Objects: 👾			
- Block Diagr	am Objects: 😌			
e e Gode:		2.e-2.6Ku: 1.		
Data: 🖈		0.9K+3		
Total: 13		. 5.4.2K ≈		
Total VI Siz	e On Disk ? 🍌 🦫	100		
164. 164 164 164 164 164 164 164 164 164 164 164 164 164 164 164 164.				97.594
Total State of the			*2   1	
	OK Ca	ncel 9E	President S	

Fig. 21



Patent Information & For the most current list of patents covering this product, please refer to ni.com/legal/patents. The LabVIEW software is covered by one or more of the following Patents: United States Patent No(s): 4,901,221; 4,914,568; 5,291,587; 5,301,301; 5,301,336; 5,475,851; 5,481,740; 5,481,741; 5,497,500; 5,504,917; 5,533,983; |5,610,828; 5,652,909; 5,732,277; 5,734,863; 5,737,622; 5,764,546; 5,784,275; 5,821,934; 5,847,953; 5,905,649; 5,920,479; 5,974,254; 5,990,906; 6,064,812; 6,064,316; 6,102,965; 6,133,270; D384051; D387750; D384050; D384052 European Patent No(s).: 0242131 Japanese Patent No(s).: 3,016,783 Canadian Patent No(s).: 1285655 Various other software products may be included with this version of LabVIEW. If any software products listed below are included, they are covered by various Patents as follows: The LabVIEW Signal Processing Toolset is covered by one or more of the following Patents: U.S. Patent No(s).: 5,353,233; 6,108,609 European Patent No(s).: 0632899 Japanese Patent No(s).: 2,697,957 The LabVIEW Datalogging and Supervisory Control Module is covered by one or more of the following Patents: U.S. Patent No(s).: 5,966,532; 6,053,951 abVIEW Real Time is covered by one or more of the following Patents: U.S. Patent No(s).: 6,173,438 The LabVIEW PID Control Toolset is covered by one or more of the following Patents: U.S. Patent No(s).: 6,081,751 The IVI Driver Toolset is covered by one or more of the following Patents: U.S. Patent No(s).: 5,963,725; 6,035,156 The NI-YISA software is covered by one or more of the following Patents: U.S. Patent No(s).: 5,724,272; 5,710,727; 5,847,955; 5,640,572; 5,771,383; 5,627,988; 5,717,614 The NI-DAQ software is covered by one or more of the following Patents: U.S. Patent No(s).: 5,619,702; 6,067,534; 6,096,094; 6,052,743; 6,143,438; 5,926,775; 5,987,530; 6,073,205 The NI-433 or NI-433.2 (NI-GPIB) software is covered by one or more of the following Patents: U.S. Patent No(s).: 5,974,541; 5,964,892; 5,958,028; 5,987,530; 6,073,205 The NI-FBUS software, including one or more of the NI-FBUS Configurator software or the NI-FBUS Monitor software, is covered by one or more of the following Patents: U.S. Patent No(s).: 5,854,890; 5,796,721; 5,850,523; 5,971,581; 6,141,596; 6,076,952; 5,973,850;




Fig. 24

Lookin	My Documents		<b>6 E</b>		
	Adobe				
M. Recent	imbosco My Archives		 	•	
Documents	圖 My Data Sources 圖My eBooks				
Desktop	My Music		 : .		
	My Pictures  My Received Files	I		. : :	
	My Webs  Wisual Studio Proj	ects			
My Documents	Shortcut to 2nd Y	ear		•	
				•	
Ny Computer		•			
Wy Network	File name				Öpen
Places	Files of type : 5 1	/ls & Controls (*.v		¥	Cancel




Fig. 26

course see a a Windows Libby that transfers mages from IWAIN devices to files in BMR or JPEG format. Because it is controlled by considering the DOS box, as a spawned sub-program or from a desktop con.

The ACQUIRE formation (Regions)

ACQUIRE (options) (Rename)

Option	Definition	Example		2213		3545				<b>1829</b>	
AUTOBRIGHTn	Set automatic brightness 1 = On, 0=Off	/autobright1								-	
ADF	Enable automatic leeding of documents	/adl	·.	•			•				
Bn	Set Brightness to n. (very device specific)	/b500	••	•							
ВМР	Write .bmp files [default]	/bmp	•	-			•				•
⁄8₩	Request 1-bit black & white	/8W .									
'cm	Set units to centimeters	/cm									•
Cn	Set Contrast to n. (very device specific)	/00	•	· ·						•	
DUP	Use duplex scanning	/dup					•				
FEEDER	Select document feeder	/Feeder			•						
GAMMAn	Set gamma to n	/Gamma1:8			•						
GRAY	Request 8-bit grayscale	/Gray									•
H or. /?	Display this help text (and exit)	n T				•				. :	
HIDE	Ask the imaging device to hide its dialog	/hide					•				
MIGHn	Set highlight value =.n	/high248	• • •			•	•	•			
Ήn	Set Height to scan (in units)	/H10									
1 or. /Inches	Set units to inches (default)	/i			•					٠.	
UPEG `	Write .jpg files (JPEG/JFIF format) with quality 75 (good)	/peg					• •				
UPEGn	Write ing files with quality n [1_100]	/ipeq50									٠.
LOG	Log internal TWAIN activity to c:\eztwain.log	/log							•		
N or /Nn	Scan multiple images (up to n)	/n /n3									•
note:	Multiple images are saved to filename1, filename2,	•							•	•	
NOINDIC	Request no progress indicators	/noindic .							: .		
NOSCAN	Don't scan	/noScan									
וטסא	Request no scan dialog (Same as /HIDE above)	/noUl :									
PAPER=3	Select paper size: A3A4A5.84,85,86,LETTER.LEGAL	/paper=84			•						
PAPER=x	Select paper type in (see TWSS_* in TWAIN.H)	/Paper=3 (letter)									
PIXELS	Set units to pixels	/pixels									
REFL	Set fight path to Reflective	/refi									
AGB	Request 24-bit color	/rgb									
An or /R=n	Set Resolution to n in pixels per unit	/1200									
SCAN	Scan an image, even if other options indicate not	/scan									
SHADOWn .	Set shadow value = n	/shadow10			•						
S=\$	Use source whose name contains the string s	/s=Fujksu		٠.			•				
ss ·	Display the TWAIN Select Source dialog (and exit)	/SS			•						
Tn ,	Set Threshold to n	/T128									•
TRANS	Set light path to Transmissive	/trans ·									
/	Display version information (and exit)	/٧									
Wn	Set Width to scan (in units)	₩6.2									
Kn	Set left edge of the scan area (units from left)	A1.5									•
Υn	Set top edge of the scan area (units from top)	N7.25				•					

# MATERIALS and METH

Human tendon internal fibroblasts (HTIF,  $2x10^5$  cells/100  $\mu$ l/ specimen) were plated in linear, tethered, collagen gels in TissueTrain TM culture plates (Figure 1).

After 2 hours, when the gels had solidified, the culture plates were removed from the FX-4000TT Tissue Train<sup>TM</sup> Culture System and placed on the glass of a Plustek OpticPro U24 flatbed scanner, in the incubator (Figure 2).





Figure 1. Specimen preparation

Gel + Cells 37°C C0<sub>2</sub> incubator



# MATERIALS and METHODS

- configured to collect images every hour for the first 4 hours International Corp., patent pending), the scanner was of each day and every 2 hours for the remainder of the day, (Flexcel ScanFlexTM program, custom for 4 days. Using
- Culture plates were only removed from the incubator once/day to change the medium
- Images were imported into SigmaScan software to the area of each gel at each time point

**BEST AVAILABLE COPY** 




Figure 4. Scan of four Tissue Train<sup>TM</sup> culture plates taken in the incubator

# RESULTS

Gels experienced the greatest rate of contraction (58.6%) in the first 24 hours, and continued contracting to a total of 73.6% by the end of Day 4.





Figure 5. Contraction curve for gels from time of plating through day



#### Document made available under the **Patent Cooperation Treaty (PCT)**

International application number: PCT/US04/035363

International filing date:

22 October 2004 (22.10.2004)

Document type:

Certified copy of priority document

Document details:

Country/Office: US

Number:

60/513,355

Filing date:

22 October 2003 (22.10.2003)

Date of receipt at the International Bureau: 15 December 2004 (15.12.2004)

Remark:

Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)



# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

#### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
D omven

#### IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.